

XR 300 T LS

Part No.: 8300006

- Load Sense





Upper	
G G3/4	G0: G 1/2

A: Ø244,7 mm	AA: 6°	B: M16	C: 33 mm	D: Ø160 mm	E: Ø216 mm	F: Ø300 mm	G: 122,3 mm	H: Ø17 mm	I: Ø270 mm	J: 45°	K: Ø295 mm	L: 206,3 mm	M: 30°
O: Ø16 mm	P: 15°	Q: M10	R: 90°	S: Ø96 mm	T: 19 mm	Y: Ø16 mm	Z: Ø230 mm						

		Max	Max	Max	Max		Max	Max	Max	Max
77 kg	360°	±300 kN[1]	±90 kN	±70 kN	±17 kNm[2]	3000 Nm	28 l/min	25 MPa	35 MPa	35 MPa

[1] Max axial load static indicate theoretical max load for hanging applications without accelerations.

[2] The bending moment may not be combined with axial load.

A rotator with the shortening LS is not equipped with restrictors (unlike our standard rotators). This means that the oil flow from the base machine has to be adapted.

When using a vibroplate and applications with corresponding requirements, connect the hydraulic hose for Pressure (P) to Grapple close (G) and connect Tank (T) to Grapple open (G0).

Pressure limiting valves fitted in the motor.

Can be supplemented with hose guard.

Oil distributor ordered separately.

We reserve the right to make product changes. For further technical information relating to integration and hydraulic connections, please contact rotator@indexator.com

Indexator Rotator Systems AB, Box 11, SE-922 21 Vindeln, Sweden
E-mail: rotator@indexator.com Tel: +46 933 148 00
PDF document generated: 2026-07-28 16:16