


XR 300 C LS


Part No.: 8300014

- Central lubrication
- Load Sense









Upper		
Central lubrication: M10 x 1,0	G: G 3/4	G0: R: G 1/2

A:	AA:	B:	C:	D:	E:	F:	G:	H:	I:	J:	K:	L:	M:
244,7 mm	6°	M20	33 mm	Ø160 mm	Ø210 mm	Ø300 mm	122,3 mm	Ø17 mm	Ø270 mm	45°	Ø295 mm	206,3 mm	30°
N:	O:	P:	Q:	R:	S:	T:	U:	Y:	Z:				
32°	Ø16 mm	15°	M10	90°	Ø96 mm	19 mm	28°	Ø16 mm	Ø230 mm				

		Max	Max	Max	Max		Max	Max	Max	Max	Max
77 kg	360°	±300 kN[1]	±90 kN	±70 kN	±17 kNm[2]	3000 Nm	28 l/min	25 MPa	35 MPa	35 MPa	40 MPa

[1] Max axial load static indicate theoretical max load for hanging applications without accelerations.

[2] The bending moment may not be combined with axial load.

A rotator with the shortening LS is not equipped with restrictors (unlike our standard rotators). This means that the oil flow from the base machine has to be adapted.

When using a vibroplate and applications with corresponding requirements, connect the hydraulic hose for Pressure (P) to Grapple close (G) and connect Tank (T) to Grapple open (G0).

Pressure limiting valves fitted in the motor.

Can be supplemented with hose guard.

Oil distributor ordered separately.

We reserve the right to make product changes. For further technical information relating to integration and hydraulic connections, please contact rotator@indexator.com

Indexator Rotator Systems AB, Box 11, SE-922 21 Vindeln, Sweden
E-mail: rotator@indexator.com Tel: +46 933 148 00
PDF document generated: 2026-07-28 16:16